| Reference Number 54028 | Driving Directions To Well | | | | Date Completed Nov 7, 1970 |
|--|------------------------------------|------------------------|--------------------|------------------------|-------------------------------|
| Owner/Contractor Well Owner | Name Ex. 6 personal | Address Ex. 6 personal | | | Telephone |
| Building Contractor Drilling Contractor | HAMILTON BROS INC. | | | | |
| Equipment Operator | TERRY HAMILTON | License: | | | |
| Construction Details | | | | | |
| Well | Use: Home | Drilling method: | Rotary | Pump type: | |
| | Depth: 59.0 ft. | Pump setting depth: | | Water quality: | |
| Casing | Length: 57.0 ft. | Material: | | Diameter: 4.00 in. | |
| Screen | Length: 2.0 ft. | Material: | | Diameter: 3.00 in. Slo | t Size: #6 |
| Well Capacity Test | | | | | |
| | Type of test: Pumping | Test rate: 10.0 gp | m for 2.0 hrs. | Bail test rate: | |
| | Drawdown: | Static water level: | | | |
| Grouting Information | | | | | |
| | Material: | | | Depth: | |
| | Installation method: | | | Number of bags used: | |
| Well Abandonment | | | | | |
| | Sealing Material: | | | Depth: | |
| | Installation method: | | | Number of bags used: | |
| Administrative | | | | | |
| | County: Marion | | Township: 15N | Range: 3E | |
| | Section: SE of the SW of the NW of | f Section 5 | | Topo map: India | napolis West |
| | Field located by: MCBN | | On: 1/1/1992 | Grant Name: | |
| | Courthouse loc. by: | | On: | Grant No.: | |
| | Loc. accpt. w/o ver. by: | | On: | | |
| | Subdivision name: | | Lot number: | | |
| | Ft W of EL: Ft N | of SL: | Ft E of WL: | Ft S of NL: | |
| | Ground elevation: 718.0 Dept | h to bedrock: | Bedrock elevation: | Aquifer eleva | ation: 658.0 |
| | UTM Easting: 565960.0 | | UTM Northing: | 4402625.0 | |
| Well Log | | | | | |
| | Тор | Bottom Formation | n | | |

| Тор | Bottom | Formation |
|-----|--------|-----------|
| 0 | 30 | CLAY |
| 30 | 40 | SAND |
| 40 | 57 | CLAY |
| 57 | 60 | SAND |

Comments

WLSR001 1 03/29/2010 1:33 PM

| Reference Number | Driving Directions To Well Do | | | | Date Completed |
|----------------------|--|--------------------|----------------------------|----------------------|----------------|
| 56682 | .5 MI W OF GASOLINE ALLEY ON COSSELL RD ON S SIDE (WHERE COSSELL RD DEAD ENDS AT HOLT RD) (4017 COSSELL RD) | | | Oct 5, 1993 | |
| Owner/Contractor | Name | Address | | | Telephone |
| Well Owner | Ex. 6 personal privacy | | | | ()241-6027 |
| Building Contractor | | | | | |
| Drilling Contractor | PERRY WELL DRILLING | 4946 SR 32 W ANI | DERSON IN 46011 | | ()642-7105 |
| Equipment Operator | JEFF FLEMING | License: 1074 | | | |
| Construction Details | | | | | |
| Well | Use: Home | Drilling method: | Rotary | Pump type: Submers | sible |
| | Depth: 260.0 ft. | Pump setting dep | oth: | Water quality: | |
| Casing | Length: 139.0 ft. | Material: | PVC | Diameter: 5.00 in. | |
| Screen | Length: | Material: | | Diameter: SI | ot Size: |
| Well Capacity Test | | | | | |
| | Type of test: Air | Test rate: 15 | .0 gpm for 1.0 hrs. | Bail test rate: | |
| | Drawdown: | Static water level | : 71.0 ft. | | |
| Grouting Information | | | | | |
| | Material: BNSL | | | Depth: 25.0 to | 80.0 ft. |
| | Installation method: TREM | | | Number of bags used: | 2.25 |
| Well Abandonment | | | | | |
| | Sealing Material: | | | Depth: | \ |
| | Installation method: | | | Number of bags used: | |
| Administrative | | | | | |
| | County: Marion | | Township: 15N | Range: 3E | |
| | Section: NW of Section 5 | | | | ywood |
| | Field located by: | | On: | Grant Name: | |
| | Courthouse loc. by: | | On: | Grant No.: | |
| | Loc. accpt. w/o ver. by: | | On: | | |
| | Subdivision name: Ft W of EL: | Ft N of SL: | Lot number: Ft E of WL: | Ft S of NL: | |
| | Ground elevation: | Depth to bedrock: | Bedrock elevation: | | vation: |
| | UTM Easting: | Deptil to bedrock. | UTM Northing: | Aquilei elev | ration. |
| Well Log | 5 m. Lasting. | | o .m rioranny. | | |
| . 3 | Тор | Bottom Forr | mation | | |
| | 0 | 3 TOF | SOIL | | |
| | 3 | 37 S& | | | |
| | 37 44 | 44 GR/ 49 S& | AY CLAY G | | |
| | 49 | 67 GR/ | AY CLAY | | |
| | 67 | 70 S & 78 GR/ | | | |
| | 70 78 | | AY CLAY (SHALE | | |
| | 136 | 260 STC | | | |
| Comments | | | | | |
| | | | | | |

WLSR001 2 03/29/2010 1:33 PM

| Reference Number | Driving Directions To Well 4019 W COSSELL RD, INDPLS IN 46222. | | | Date Completed Sep 5, 1975 | |
|----------------------|--|-------------------|-------------------------|-------------------------------|-------------------------|
| Owner/Contractor | Name | Address | | | Telephone |
| Well Owner | Ex. 6 personal privacy | | | | |
| Building Contractor | | | | | |
| Drilling Contractor | CLAYTON OTTINGER WM STOVALL | • | 62, ZIONSVILLE IN 46077 | | |
| Equipment Operator | WWISTOVALL | License: | | | |
| Construction Details | | | | | |
| Well | Use: Home | Drilling meth | nod: Cable Tool | Pump type: | |
| | Depth: 41.0 ft. | Pump setting | | Water quality: | |
| Casing | Length: 41.0 ft. | Material: | | Diameter: 4.00 in. | |
| Screen | Length: | Material: | | Diameter: | Slot Size: #40 COOKS |
| Well Consoity Test | | | | | COOKS |
| Well Capacity Test | Type of test: Pumping | Test rate: | 10.0 gpm for 2.0 hrs. | Bail test rate: | |
| | Drawdown: 8.0 ft. | Static water | | Dui tost ruto. | |
| Grouting Information | | | | | |
| | Material: | | | Depth: | |
| | Installation method: | | | Number of bags use | ed: |
| Well Abandonment | | | | | |
| | Sealing Material: | | | Depth: | |
| | Installation method: | | | Number of bags use | ed: |
| Administrative | | | | | |
| | County: Marion | | Township: 15N | Range: 3E | |
| | Section: NE of the SW of Se | ction 5 | | Topo map: | Indianapolis West |
| | Field located by: | | On: On: | Grant Name: Grant No.: | |
| | Courthouse loc. by: Loc. accpt. w/o ver. by: TM | IR. | On: 9/15/1975 | Grant No | |
| | Subdivision name: | | Lot number: | | |
| | Ft W of EL: | Ft N of SL: | Ft E of WL: | Ft S of I | NL: |
| | Ground elevation: | Depth to bedrock: | Bedrock elevation | : Aquifer | elevation: |
| | UTM Easting: | | UTM Northing: | | |
| Well Log | | | | | |
| | Тор | Bottom | Formation | | |
| | 0 6 | 6 15 | BR CLAY DRY GRAV | | |
| | 15 | 18 | BR CLAY & GRAV | | |
| | 18 | 23 | SAND WATER | | |
| | 23 25 | 25 41 | GRAY CLAY WATER GRAV | | |
| Comments | 20 | | | | |
| 231111101113 | | | | | |

WLSR001 3 03/29/2010 1:33 PM

| Reference Number 180241 | Driving Directions To Well | | | Date Completed Jan 30, 1973 |
|-----------------------------|--------------------------------|---------------------|--------------------|---|
| Owner/Contractor Well Owner | Name Ex. 6 personal privacy | Address | | Telephone |
| Building Contractor | | | | |
| Drilling Contractor | HAMILTON BROS INC | Linner | | |
| Equipment Operator | RASH | License: | | |
| Construction Details | | | | |
| Well | Use: Home | Drilling method: | Cable Tool | Pump type: |
| | Depth: 51.0 ft. | Pump setting depth | | Water quality: |
| Casing | Length: 51.0 ft. | Material: | | Diameter: 4.00 in. |
| Screen | Length: 3.0 ft. | Material: | | Diameter: 4.00 in. Slot Size: |
| Well Capacity Test | | | | |
| | Type of test: | Test rate: | | Bail test rate: 10.0 gpm for 5.0 hrs. |
| | Drawdown: | Static water level: | | |
| Grouting Information | | | | |
| | Material: | | | Depth: |
| | Installation method: | | | Number of bags used: |
| Well Abandonment | | | | |
| | Sealing Material: | | | Depth: |
| | Installation method: | | | Number of bags used: |
| Administrative | | | T 1: 451 | |
| | County: Marion | | Township: 15N | Range: 3E |
| | Section: 5 Field located by: | | On: | Topo map: Indianapolis West Grant Name: |
| | Courthouse loc. by: | | On: | Grant No.: |
| | Loc. accpt. w/o ver. by: | | On: | Grant No |
| | Subdivision name: | | Lot number: | |
| | Ft W of EL: | Ft N of SL: | Ft E of WL: | Ft S of NL: |
| | Ground elevation: | Depth to bedrock: | Bedrock elevation: | : Aquifer elevation: |
| | UTM Easting: | | UTM Northing: | |
| Well Log | | | | |
| | Тор | Bottom Forma | | |
| | 0 5 | 5 TOPS 35 SAND | OIL & CLAY | |
| | 35 | 51 CLAY | | |
| Comments | | | | |

WLSR001 4 03/29/2010 1:33 PM

Reference Number **Driving Directions To Well Date Completed** BETWEEN REONA & HOLT RD. OFF MICHIGAN Oct 28, 1979 180590 Owner/Contractor Name Address Telephone Well Owner **Building Contractor Drilling Contractor Equipment Operator** JOHN AUFDERHEIDE License: Construction Details Well Use: Home Drilling method: Cable Pump type: Tool Pump setting depth: 40.0 ft. Depth: Water quality: CLEAR Length: 50.0 ft. Material: Diameter: 4.00 in. Casing Material: Diameter: 3.00 in. Slot Size: 30 Length: 5.0 ft. Screen Well Capacity Test Type of test: Bailing Test rate: 10.0 gpm for 1.0 hrs. Bail test rate: Drawdown: 12.0 ft. Static water level: 23.0 ft. **Grouting Information** Material: Depth: Installation method: Number of bags used: Well Abandonment Sealing Material: Depth: Installation method: Number of bags used: Administrative Township: 15N Range: 3E County: Marion Section: SE of the NW of Section 5 Topo map: Indianapolis West Field located by: On: Grant Name: On: Grant No.: Courthouse loc. by: Loc. accpt. w/o ver. by: TCS On: Subdivision name: Lot number: Ft E of WL: Ft W of EL: Ft N of SL: Ft S of NL: Ground elevation: Depth to bedrock: Bedrock elevation: Aquifer elevation: **UTM Easting: UTM Northing:** Well Log

| Top | Bottom | Formation |
|-----|--------|---------------|
| 0 | 10 | CLAY |
| 10 | 35 | SAND & GRAVEL |
| 35 | 45 | CLAY |
| 45 | 49 | SOUPY SAND |
| 49 | 52 | SAND & GRAVEL |

Comments

WLSR001 5 03/29/2010 1:33 PM